



ALUMINUM ELECTROLYTIC CAPACITORS

RADIAL LEAD TAPING

Lead Taping Capacitors for Automatic Insertion

■ STANDARD

Code	Case range		Dimensions				Form	External form Drawing	Packing Form
	ΦD	L (max)	H ± 0.75	Ho ± 0.5	F ± 0.5	P ± 0.1			
FF	4~6	5~13	18.5	--	2.5	12.7	A		
	8	5~13	18.5	--	3.5	12.7	A		
	4~8	5~7	17.5	16	5.0	12.7	B		
	5~6.3	11~13	18.5						
	8	11~22	20.0	5.0	12.7	A			
	10	11~22	18.5	--	15.0	A			
	12.5	16~27	18.5	--	15.0	A			
16~18	20~27	18.5	--	7.5	30.0	C			

LEAD CUT AND FORMING

<p>Lead Configuration:FC($\Phi 4, 5, 6, 3, 8$)</p>	<p>Lead Configuration:FM($\Phi 4, 5, 6, 3, 8$)</p>	<p>Lead Configuration:($\Phi 3, 4, 5, 6, 3, 8$)</p>						
<p>Lead Configuration:CC($\Phi 10, 12.5, 16, 18$)</p>	<p>Lead Configuration:MC($\Phi 10, 12.5, 16, 18$)</p> <table border="1"> <thead> <tr> <th>ΦD</th> <th>f± 0.1</th> </tr> </thead> <tbody> <tr> <td>$\Phi 10, 12.5$</td> <td>1.1</td> </tr> <tr> <td>$\Phi 16, 18$</td> <td>1.3</td> </tr> </tbody> </table>	ΦD	f ± 0.1	$\Phi 10, 12.5$	1.1	$\Phi 16, 18$	1.3	<p>Lead Configuration:($\Phi 3, 4, 5, 6, 3, 8$)</p>
ΦD	f ± 0.1							
$\Phi 10, 12.5$	1.1							
$\Phi 16, 18$	1.3							